



Contact Us

For pricing
and application information
631-232-0002

In stock and ready to ship!

Twin Screw Stuffer Model# 12DSS7.5I Serial# 25

Quick and accurate delivery of high viscosity product (ex. Icings, Jam, Fig, Butter, Cream Cheese) to your process. Easy product loading with a built-in 200 gal stainless steel holding tank. Digital controls monitor screw rpm to ensure constant pressure at the pump inlet regardless of production rate (up to 6000 lbs/hour). This model is jacketed for heating or cooling.

About this model:

- Power: 460VAC, 3PHASE, 60HZ
- Operator Control Box w/PLC
- SST NEMA4 Electrical Enclosure w/Tach
- 200 Gal SST Holding Tank
- Jacketed Tank for Cooling/Heating
- 7.5HP TEFC Gear Motor
- 7.5HP AC Variable Frequency Drive
- SST Base Plate I-Beam Support/Adjustable Legs
- Pump Assy Mounted Separately on Casters
- Screw extractor/carriage for disassembly, cleaning and re-assembly
- Pressure Transducer to monitor Pump Pressure
- Twin 12" Stainless Steel Screws

Options Include:

- In-Line Magnetic Trap
- NEMA4X SST Variable Frequency Drive
- Positive Displacement Waukesha Pump
- Model 64PA7.5I Pump Assy
- Mounted on Stainless Steel Baseplate with casters



E.T. OAKES CORPORATION

686 Old Willets Path Hauppauge, NY 11788
tel: (631) 232-0002 fax: (631) 232-0170
e-mail: info@oakes.com www.oakes.com